

F A B T E X[®]

C A R E A N D W A R R A N T Y

Shower Curtains

FABRICS

Wash Cycle

Wash as any standard colored fabric, with temperatures not exceeding 160°F using synthetic detergent. Do not use bleach or fabric softener. Do not extract. A 30 second spin may be used to extract excess moisture. Remove the load immediately.

Drying Cycle

Do not overload the dryer. Tumble dry 3 to 5 minutes on a synthetic cycle (110°F.) until damp dry and remove immediately. As with all polyester fabrics, excessive heat will detract from the permanent press characteristics of this fabric.

Finishing

If the fabric is folded after the drying cycle, no finishing is required. Occasional, light touch-up with a hand iron (at 275°F. maximum), or with a flat bed press with a covered head may be desired for smoother seams. Use a cover cloth between the fabric and iron/pressing head. Avoid prolonged contact with heat. Do not use caustic soap or bleach. Do not put through a mangler.

Shower Curtains

VINYL

Fabtex vinyl healthcare fabrics offer “clean-in place” convenience. Any soils or stains that may accumulate on the vinyl’s surfaces should be removed periodically for a fresh new appearance. Use neutral soap suds and lukewarm water. Then rinse with water and allow the vinyl to dry.

Spot and Stain Cleaning

Standard household/vinyl cleansers and/or a soft bristle brush can be used for removing troublesome spots or stains. Heavy “dried on” soil may first require soaking to loosen. **DO NOT USE HARSH CLEANSERS OR SOLVENTS.**

Laundering

Fabtex does not recommend the laundering of vinyl fabrics since laundering may substantially decrease the useful life of these fabrics. However, if laundering is required, follow the procedures of the International Fabricare Institute:

- a. Wash and rinse according to the “Synthetic Washing Procedure for Coated Fabrics” with temperatures not exceeding 100°F. (See below).
- b. Extract water with a centrifugal extractor.
- c. Tumble dry in a steam dryer (not gas) at 120°F maximum. For tailored, fitted items, tumble dry without heat or simply air dry. **DO NOT IRON.**

OPERATION	WATER LEVEL	TIME	MAXIMUM TEMPERATURE	SUPPLIES
1 st suds	High	5 mins	100°F	Neutral Soap & Alkali
2 nd suds	High	10 mins	100°F	Neutral Soap & Alkali
1 st suds	High	3 mins	100°F	Water
2 nd suds	Low	3 mins	90°F	Sour to pH 5.0

Use a slow speed machine. Stop the wash wheel for draining and refilling between each cycle.

Limited Warranty

Fabtex warrants its products from the date of shipment to be free from defects in materials and workmanship under normal and proper for a period of 90 days.

Shower curtains that are treated with an antimicrobial finish or are otherwise antimicrobial rated are also warrantied against mildew and bacteria growth, under normal usage, and with the proper maintenance by the consumer in accordance with the listed care instructions.

Fabtex's only obligation shall be to repair or replace defective product, which does not conform to the warranty. Fabtex shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of, or the inability to use the product. Before using, the Buyer and/or the ultimate User shall determine the suitability of the project for its intended use, and User assumes all risks and liability in connection therewith.

The articles that are replaced pursuant to the terms of this warranty shall be retained by Fabtex, and the User is responsible for any freight costs related to the repair or replacement. The foregoing warranty is exclusive and in lieu of all other warranties of quality, whether written, oral or implied (including any other warranty of merchantability or fitness or purchase).

The following are exclusions from warranty:

- If the product has been opened, dismantled or returned with clear evidence of abuse or other damage.
- If usage, adaptation or installation are not in accordance with our installation and operating instructions.
- If our written specifications are not properly applied by the Buyer when selecting the equipment.
- If hardware and/or equipment has been improperly or inadequately installed.
- If our equipment has been used to perform a function other than the function it was designed to handle or exceeds its rated capacity.
- If our written instructions for installation have not been followed.

All costs related to installation and reinstallation of the Fabtex equipment covered by this warranty are not the responsibility of Fabtex. Fabtex will not be responsible for any consequential damages during or following installation procedures.

If the buyer resells any Fabtex products to another Buyer or End-user, it shall include all of the terms and provisions of this warranty in such resale.

Fabtex's responsibility to any such Third Party shall be no greater than Fabtex's responsibility under the warranty to the original Buyer.

No returns will be accepted without prior written authorization by Fabtex. All returns must be accompanied by a Return Authorization Number issued. To contact customer service, call toll free (800) 778-2791.